

# AGRIMAX RT 855

|           |                                                                                 |
|-----------|---------------------------------------------------------------------------------|
| TIRE SIZE | 320/85 R 32                                                                     |
| UM        | IS STANDARD                                                                     |
| MACHINERY | PULVERIZADOR / VENDIMIADORA /<br>TRACTOR / COSECHADORA /<br>MAQUINARIA AGRÍCOLA |
| VERSIÓN   | SPECIAL                                                                         |
| TIRE TYPE | TL                                                                              |
| LI/SS     | 126 A8/B                                                                        |

## DIMENSIONES IS STANDARD

|          |      |         |                |
|----------|------|---------|----------------|
| SW (MM)  | 329  | RIM REC | W 11           |
| OD (MM)  | 1357 | RIM ALT | W 9 ; W 10     |
| SLR (MM) | 621  | ECE     | E4-106R-000758 |
| RC (MM)  | 4081 | SRI     | 650            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|------------|------|------|------|------|------|------|
| 50         | 935  | 1090 | 1245 | 1395 | 1550 | 1700 |
| 40         | 935  | 1090 | 1245 | 1395 | 1550 | 1700 |
| 30         | 1005 | 1165 | 1330 | 1495 | 1660 | 1820 |
| 10 LT      | 1255 | 1460 | 1665 | 1870 | 2075 | 2280 |
| 10 HT      | 1005 | 1165 | 1330 | 1495 | 1660 | 1820 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

