

# EM 937 E3 (L)

|                     |                                                                                        |
|---------------------|----------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>    | <b>14.00 - 25</b>                                                                      |
| <b>UM</b>           | US STANDARD                                                                            |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | CHARGEUSE-PELLETEUSE /<br>CHARGEUR                                                     |
| <b>VERSION</b>      | STANDARD                                                                               |
| <b>TIRE TYPE</b>    | TT                                                                                     |



## DIMENSIONS US STANDARD

|                 |          |                 |           |
|-----------------|----------|-----------------|-----------|
| <b>CODE USA</b> | 94015429 | <b>RIM REC</b>  | 10.00/1.5 |
| <b>OD (IN)</b>  | 53.9     | <b>PR</b>       | 24        |
| <b>SLR (IN)</b> | 24.4     | <b>TRA CODE</b> | E3/L3     |
| <b>RC (IN)</b>  | 161.6    |                 |           |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 83    | 123   |
|-----------|-------|-------|
| 30        | 11400 | -     |
| 5         | -     | 20900 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.