

# AGRIMAX RT 855

<b>TIRE SIZE</b>	250/85 R 20
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	BESPRUTNINGSBIL / SKÖRDEMASKIN FÖR VINGÅRD / TRAKTOR / SKÖRDEMASKIN / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	116 A8/B



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	250	<b>RIM REC</b>	W 8
<b>OD (MM)</b>	940	<b>RIM ALT</b>	W 7 ; W 9
<b>SLR (MM)</b>	424	<b>ECE</b>	E4-106R-000639
<b>RC (MM)</b>	2812	<b>SRI</b>	450

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	590	675	775	875	975	1075	1165	1250
40	590	675	775	875	975	1075	1165	1250
30	630	725	835	940	1050	1155	1250	1340
10 LT	790	905	1040	1175	1310	1445	1560	1675
10 HT	630	725	835	940	1050	1155	1250	1340

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.