


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>480/80 R 46</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	FELDSPRITZE / TRAUBENERNTEMASCHINE / TRACTOR / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	164 A8/B



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	479	<b>RIM REC</b>	DW 16 A ; W 16 A ; DD 16
<b>OD (MM)</b>	1936	<b>RIM ALT</b>	W 16 L ; DD 16 L ; DW 16 L
<b>SLR (MM)</b>	895	<b>ECE</b>	E4-106R-000798
<b>RC (MM)</b>	5871	<b>SRI</b>	925

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
<b>50</b>	2295	2635	2975	3315	3655	3955	4250	4650	5000
<b>40</b>	2295	2635	2975	3315	3655	3955	4250	4650	5000
<b>30</b>	2460	2825	3185	3550	3915	4235	4550	4975	5350
<b>10 LT</b>	3080	3535	3990	4445	4900	5300	5695	6230	6700
<b>10 HT</b>	2460	2825	3185	3550	3915	4235	4550	4975	5350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.