

AGRIMAX RT 657

TIRE SIZE	420/65 R 20
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	VENDEMMIATRICE / TRATTORE / MIETITREBBIA
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS	135 D ; 138 A8



DIMENSIONI IS STANDARD

SW (MM)	418	RIM REC	W 13
OD (MM)	1054	RIM ALT	W 11 ; W 12
SLR (MM)	468	ECE	E4-106R-001390
RC (MM)	3162	SRI	500

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1025	1200	1375	1530	1680	1810	2010	2180
50	1080	1260	1445	1605	1765	1905	2110	2290
40	1110	1300	1490	1655	1820	1960	2175	2360
30	1180	1385	1585	1760	1935	2085	2310	2510
10 LT	1375	1610	1845	2050	2255	2430	2695	2925
10 HT	1180	1385	1585	1760	1935	2085	2310	2510

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.