

# AW 705

<b>TIRE SIZE</b>	<b>16.0/70 - 20</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	PRESĂ DE BALOTAT / MAȘINI DE IMPLEMENTARE / REMORCĂ / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS FREE ROLLING</b>	154 A8



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	408	<b>RIM REC</b>	13.0
<b>OD (MM)</b>	1075	<b>RIM ALT</b>	12 SDC; 13 SDC; 14
<b>SLR (MM)</b>	480	<b>ECE</b>	E11-106R-003368
<b>RC (MM)</b>	3155	<b>PR</b>	14

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>3.50</b>
10 FR	5250
25 FR	4465
30 FR	4200
40 FR	3750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.