


MULTIMAX MP 540

| | |
|---------------------|--|
| TYRE SIZE | 335/80 R 20 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | UNIVERSAL VEHICLE / UNIVERSAL VEHICLE |
| VERSION | STANDARD |
| TYRE TYPE | TL |
| LI/SS | 149 K |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94033539 | RIM REC | 11 |
| OD (IN) | 41.1 | ECE | E11-54R-0015909 |
| SLR (IN) | 19.4 | | |
| RC (IN) | 128.3 | | |

LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 58 | 65 | 73 | 80 | 87 | 94 |
|-----------|------|------|------|------|------|------|
| 68 | 4860 | 5335 | 5810 | 6270 | 6725 | 7165 |
| 60 | 4860 | 5335 | 5810 | 6270 | 6725 | 7165 |
| 55 | 4960 | 5445 | 5920 | 6395 | 6855 | 7310 |
| 50 | 5050 | 5555 | 6040 | 6515 | 6990 | 7450 |
| 45 | 5205 | 5720 | 6215 | 6715 | 7200 | 7670 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.