


AW 09

| | |
|---------------------------|--|
| TYRE SIZE | 400/60 - 15.5 |
| UM | IS STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | IMPLEMENT MACHINERY / TRAILER / HAY HARVESTER / IMPLEMENTS |
| VERSION | STANDARD |
| TYRE TYPE | TL |
| LI/SS DRIVE WHEEL | 132 A8 |
| LI/SS FREE ROLLING | 145 A8 |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 404 | RIM REC | AG 13.00 |
| OD (MM) | 874 | ECE | E4-106R-000381 |
| SLR (MM) | 382 | | |
| RC (MM) | 2561 | | |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 3.60 |
|-------------------|-------------|
| 10 FR | 4060 |
| 25 FR | 3450 |
| 30 FR | 3250 |
| 40 FR | 2900 |
| 10 DW | 2800 |
| 25 DW | 2380 |
| 30 DW | 2240 |
| 40 DW | 2000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.