


AGRIMAX RT 600

| | |
|---------------------|--|
| TYRE SIZE | 650/65 R 38 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | HARVESTER / SPREADER / TRACTOR / IMPLEMENTS |
| VERSION | STANDARD |
| TYRE TYPE | TL |
| LI/SS | 157 D ; 160 AB |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94053667 | RC (IN) | 214.3 |
| SW (IN) | 25.4 | RIM REC | DW 20 B |
| OD (IN) | 71.3 | ECE | E11-106R-002990 |
| SLR (IN) | 32.8 | | |

LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|------|------|-------|-------|-------|
| 40 | 5090 | 6010 | 6820 | 7640 | 8370 | 9090 |
| 30 | 5360 | 6320 | 7180 | 8040 | 8800 | 9560 |
| 25 | 5560 | 6550 | 7440 | 8330 | 9130 | 9920 |
| 20 | 5860 | 6910 | 7850 | 8800 | 9630 | 10460 |
| 5 LT | 6830 | 8050 | 9150 | 10250 | 11220 | 12190 |
| 5 HT | 5860 | 6910 | 7850 | 8800 | 9630 | 10460 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.