


# AGRIMAX TERIS



<b>TIRE SIZE</b>	<b>620/75 R 26 CHO</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	COSECHADORA / COSECHADORA DE ALGODÓN
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	166 A8/B

## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94035809	<b>RC (IN)</b>	191.0
<b>SW (IN)</b>	24.6	<b>RIM REC</b>	DW 20 B
<b>OD (IN)</b>	62.6	<b>ECE</b>	E4-106R-001419
<b>SLR (IN)</b>	28.7		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	20	23	29	35	41	46
30	5380	6190	7590	8300	9120	9930	10760	11680
25	5380	6190	7590	8300	9120	9930	10760	11680
20	5760	6640	8130	8880	9770	10640	11520	12510
10 CYC	8870	10220	12530	13690	15050	16390	17750	19280
5 CYC	9680	11150	13680	14940	16410	17880	19360	21030

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.