

AGRIMAX RT 600



| | |
|---------------------|--|
| TIRE SIZE | IF 710/75 R 34 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | КОМБАЙН / РАЗБРАСЫВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ |
| VERSION | STEEL BELTED |
| TIRE TYPE | TL |
| LI/SS | 184 A8/B |

РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|------|----------------|------------------|
| SW (MM) | 715 | RIM REC | DW25 B |
| OD (MM) | 1920 | RIM ALT | DW23 B |
| SLR (MM) | 856 | ECE | E11-106R-0010577 |
| RC (MM) | 5771 | SRI | 900 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 |
|-------------|------|------|------|------|-------|-------|-------|-------|-------|-------|
| 50 | 3510 | 4140 | 4770 | 5310 | 5940 | 6480 | 7110 | 7650 | 8370 | 9000 |
| 40 | 3510 | 4140 | 4770 | 5310 | 5940 | 6480 | 7110 | 7650 | 8370 | 9000 |
| 30 | 3655 | 4310 | 4965 | 5525 | 6180 | 6740 | 7395 | 7960 | 8705 | 9360 |
| 10 | 4460 | 5260 | 6060 | 6745 | 7545 | 8230 | 9030 | 9720 | 10630 | 11430 |
| UPTO 30 CYC | 4565 | 5385 | 6205 | 6905 | 7725 | 8425 | 9245 | 9945 | 10885 | 11700 |
| UPTO 15 CYC | 5445 | 6420 | 7395 | 8235 | 9210 | 10045 | 11025 | 11860 | 12975 | 13950 |
| UPTO 10 CYC | 5970 | 7040 | 8110 | 9030 | 10100 | 11020 | 12090 | 13005 | 14230 | 15300 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.