


# AGRIMAX RT 657

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>540/65 R 30</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | VINDIMADORA / TRATOR / CEIFEIRA  |
| <b>VERSÃO</b>       | SPECIAL  |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 150 D ; 153 A8   |



## DIMENSÕES IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 530  | <b>RIM REC</b> | W 16 L         |
| <b>OD (MM)</b>  | 1464 | <b>RIM ALT</b> | W 18 L         |
| <b>SLR (MM)</b> | 670  | <b>ECE</b>     | E4-106R-000651 |
| <b>RC (MM)</b>  | 4403 | <b>SRI</b>     | 700            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|------------|------|------|------|------|------|------|------|------|
| 65         | 1610 | 1880 | 2115 | 2345 | 2580 | 2785 | 3085 | 3350 |
| 50         | 1690 | 1975 | 2220 | 2465 | 2715 | 2925 | 3240 | 3520 |
| 40         | 1755 | 2045 | 2300 | 2555 | 2815 | 3030 | 3360 | 3650 |
| 30         | 1855 | 2160 | 2430 | 2700 | 2970 | 3200 | 3550 | 3855 |
| 10 LT      | 2160 | 2515 | 2830 | 3145 | 3460 | 3730 | 4135 | 4490 |
| 10 HT      | 1855 | 2160 | 2430 | 2700 | 2970 | 3200 | 3550 | 3855 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.