


RT 747 AGRO INDUSTRIAL

| | |
|---------------------|--|
| TIRE SIZE | 460/70 R 24 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | COMPACT LOADER / TELEHANDLER / COMPACT LOADER / TELEHANDLER |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 152 A8/B |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|------------------|
| USA CODE | 94016815 | RC (IN) | 151.2 |
| SW (IN) | 18.3 | RIM REC | DW 15 L |
| OD (IN) | 49.4 | RIM ALT | DW 14 L; DW 16 L |
| SLR (IN) | 21.9 | ECE | E11-106R-004071 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 17 | 23 | 29 | 35 | 41 | 46 |
|-----------|------|------|-------|-------|-------|-------|
| 30 | 3680 | 4540 | 5320 | 6180 | 6970 | 7830 |
| 25 | 3680 | 4540 | 5320 | 6180 | 6970 | 7830 |
| 20 | 3940 | 4860 | 5700 | 6610 | 7450 | 8380 |
| 15 | 4080 | 5040 | 5910 | 6870 | 7730 | 8690 |
| 5 CYC | 5520 | 6810 | 7980 | 9270 | 10450 | 11740 |
| STATIC | 7730 | 9530 | 11180 | 12980 | 14630 | 16430 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.