

FLOTATION 648

TIRE SIZE	850/50 - 30.5
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	PRESSE À PAILLE / MOISSONNEUSE / ÉPANDEUR / MOISSONNEUSE / OUTILLAGE AGRICOLE
VERSION	HD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	174 A8/170 B
LI/SS FREE ROLLING	186 A8/182 B



DIMENSIONS IS STANDARD

SW (MM)	850	RIM REC	AG 28.00
OD (MM)	1650	ECE	E11-106R-004565
SLR (MM)	710	PR	16
RC (MM)	4935		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.80	2.00	2.20
10 FR	11830	12580	13300
20 FR	10645	11320	11970
30 FR	9465	10065	10640
40 FR	8450	8985	9500
50 FR	7605	8085	8500
10 DW	8345	8870	9380
20 DW	7510	7980	8440
30 DW	6675	7095	7505
40 DW	5960	6335	6700
50 DW	5365	5700	6000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.