


# RIDEMAX FL 693 M



<b>TIRE SIZE</b>	710/35 R 22.5
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	CISTERNA MÓVEL / REBOQUE / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	157 D ; 154 E

## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	712	<b>RIM REC</b>	AG 24.00
<b>OD (MM)</b>	1070	<b>ECE</b>	E11-106R-004758
<b>SLR (MM)</b>	482	<b>SRI</b>	525
<b>RC (MM)</b>	3254		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1370	1540	1915	2175	2515	2850	3115	3415	3750
65	1510	1695	2105	2395	2765	3135	3425	3755	4125
50	1825	2050	2550	2900	3350	3800	4150	4550	4995
40	2050	2305	2865	3255	3760	4265	4660	5110	5610
30	2275	3555	3180	3615	4175	4735	5175	5670	6230
25	2380	2675	3330	3785	4370	4960	5415	5935	6520
10	2715	3045	3790	4310	4975	5645	6165	6760	7425

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.