


AGRIMAX RT 855

| | |
|---------------------|--|
| TIRE SIZE | 420/85 R 38 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | FELDSPRITZE / TRAUBENERNTEMASCHINE / TRACTOR / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 144 A8/B |



ABMESSUNGEN IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 438 | RIM REC | W 15 L |
| OD (MM) | 1679 | RIM ALT | W 13; W 14 L |
| SLR (MM) | 763 | ECE | E4-106R-000661 |
| RC (MM) | 5014 | SRI | 800 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 50 | 1540 | 1795 | 2045 | 2300 | 2550 | 2800 |
| 40 | 1540 | 1795 | 2045 | 2300 | 2550 | 2800 |
| 30 | 1650 | 1920 | 2190 | 2460 | 2730 | 3000 |
| 10 LT | 2070 | 2405 | 2745 | 3080 | 3420 | 3755 |
| 10 HT | 1650 | 1920 | 2190 | 2460 | 2730 | 3000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.