


# AS 504

<b>TIRE SIZE</b>	<b>15.5/80 - 24</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	SOLLEVATORE TELESOPICO / RIMORCHIO DA CAMPO / ATTREZZI AGRICOLI / SOLLEVATORE TELESOPICO
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	148 A8
<b>LI/SS FREE ROLLING</b>	160 A8



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	384	<b>RIM REC</b>	W 12
<b>OD (MM)</b>	1262	<b>RIM ALT</b>	W 13; W 14 L
<b>SLR (MM)</b>	570	<b>ECE</b>	E4-106R-002816
<b>RC (MM)</b>	3875	<b>PR</b>	14

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.50
10 FR	6300
25 FR	5355
30 FR	5040
40 FR	4500
10 DW	4410
25 DW	3750
30 DW	3530
40 DW	3150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.