


# RIDEMAX FL 693 M



<b>TIRE SIZE</b>	<b>650/50 R 22.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	CISTERNĂ / REMORCĂ / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	168 D

## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	645	<b>RIM REC</b>	AG 20.00
<b>OD (MM)</b>	1222	<b>ECE</b>	E11-106R-006489
<b>SLR (MM)</b>	535	<b>SRI</b>	575
<b>RC (MM)</b>	3715		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0
70	1480	1890	2295	2605	3010	3420	3775	4135	4540	5100
65	1625	2075	2520	2860	3305	3755	4145	4540	4985	5600
50	1970	2510	3080	3460	4005	4545	5020	5495	6035	6780
40	2210	2820	3465	3890	4500	5110	5640	6175	6785	7620
30	2455	3135	3845	4315	4995	5670	6265	6855	7530	8460
25	2570	3275	4020	4515	5225	5930	6550	7170	7880	8850
10	2925	3730	4580	5145	5950	6755	7460	8165	8975	10080

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.