


AGRIMAX SPARGO

TIRE SIZE	VF 480/80 R 46 CFO
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRAKTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	177 D



DIMENSIONER IS STANDARD

SW (MM)	479	RIM REC	DW 16 L
OD (MM)	1936	RIM ALT	DW 15 L
SLR (MM)	892	ECE	E11-106R-004756-01
RC (MM)	5907	SRI	925

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.4	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6
70	3715	4115	4515	4710	4980	5110	5245	5510	5775	5975	6240	6440	6640
FROM 65 TO 40	4085	4525	4960	5180	5475	5620	5765	6055	6350	6570	6860	7080	7300
30	4165	4615	5060	5285	5580	5730	5880	6175	6475	6700	6995	7220	7445
20	4250	4705	5160	5385	5690	5840	5995	6295	6600	6830	7130	7360	7590
10*	4495	4975	5460	5700	6020	6180	6340	6660	6985	7225	7545	7785	8030
UPTO 15 CYC.	17685	15965	14565	13945	13195	12855	12530	11930	11380	10995	10530	10205	9895
UPTO 30 CYC.	14810	13370	12195	11680	11050	10765	10495	9990	9525	9210	8820	8545	8285

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.