


# RIDEMAX IT 696

<b>TIRE SIZE</b>	<b>420/65 R 24 IND</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	146 D ; 151 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	418	<b>RIM REC</b>	DW 13 L ; W13
<b>OD (MM)</b>	1158	<b>RIM ALT</b>	DW 15 L ; DW 14 L
<b>SLR (MM)</b>	530	<b>ECE</b>	E11-106R-005952
<b>RC (MM)</b>	3483	<b>SRI</b>	550

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
65	1200	1470	1650	1950	2220	2490	2730	3000
50	1295	1590	1780	2105	2400	2690	2950	3240
40	1380	1690	1900	2245	2555	2865	3140	3450
30	1440	1765	1980	2340	2665	2990	3275	3600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.