


# AS 504

<b>TIRE SIZE</b>	<b>400/50 - 15</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	SOLLEVATORE TELESOPICO / RIMORCHIO DA CAMPO / ATTREZZI AGRICOLI / SOLLEVATORE TELESOPICO
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	109 A8
<b>LI/SS FREE ROLLING</b>	121 A8



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94060092	<b>RC (IN)</b>	94.0
<b>SW (IN)</b>	15.6	<b>RIM REC</b>	13 LB
<b>OD (IN)</b>	31.1	<b>ECE</b>	E11-106R-005494
<b>SLR (IN)</b>	14.5		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	44
5 FR	4480
15 FR	3800
20 FR	3580
25 FR	3200
5 DW	3170
15 DW	2700
20 DW	2550
25 DW	2270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.