


# AGRIMAX TERIS

<b>TIRE SIZE</b>	<b>650/75 R 32 CHO</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HARVESTER / COTTON PICKER
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	172 A8/B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	670	<b>RIM REC</b>	DW 21 B
<b>OD (MM)</b>	1795	<b>RIM ALT</b>	DW 20 B ; DW 23 B
<b>SLR (MM)</b>	816	<b>ECE</b>	E4-106R-001425
<b>RC (MM)</b>	5378	<b>SRI</b>	850

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2
50	2900	3340	4095	4475	4915	5355	5800	6300
40	2900	3340	4095	4475	4915	5355	5800	6300
30	3105	3575	4385	4790	5265	5735	6210	6745
15 CYC	4785	5510	6760	7385	8110	8840	9565	10395
10 CYC	5220	6015	7375	8055	8850	9640	10435	11340

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.