



## DATA SHEET

Última  
actualización  
11-07-2026

# TR 135

|                  |                    |
|------------------|--------------------|
| <b>TIRE SIZE</b> | <b>13.6 - 36</b>   |
| <b>UM</b>        | US STANDARD        |
| <b>MACHINERY</b> | TRACTOR / REMOLQUE |
| <b>VERSIÓN</b>   | STANDARD           |
| <b>TIRE TYPE</b> | TT                 |
| <b>LI/SS</b>     | 125 A8             |



### DIMENSIONES US STANDARD

|                   |          |                |                |
|-------------------|----------|----------------|----------------|
| <b>CÓDIGO USA</b> | 94003372 | <b>RC (IN)</b> | 184.5          |
| <b>SW (IN)</b>    | 13.6     | <b>RIM REC</b> | W 12           |
| <b>OD (IN)</b>    | 59.6     | <b>RIM ALT</b> | W 11           |
| <b>SLR (IN)</b>   | 28.0     | <b>ECE</b>     | E4-106R-002037 |

### LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>30</b> |
|------------------|-----------|
| 25               | 3640      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.