

FLOTATION TR 675

| | |
|---------------------------|--------------------------------------------|
| TIRE SIZE | 500/60 - 22.5 |
| UM | IS STANDARD |
| CONSTRUCTION | ❖ BIAS |
| MACHINERY | IMPLEMENT MACHINERY / TRAILER / IMPLEMENTS |
| VERSION | DUAL BEAD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 155 A8/151 B |
| LI/SS FREE ROLLING | 168 A8/164 B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 515 | RIM REC | AG 16.00 |
| OD (MM) | 1181 | RIM ALT | 15.00; 17.00 |
| SLR (MM) | 542 | ECE | E11-106R-004395 |
| RC (MM) | 3604 | PR | 20 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.70 | 3.80 | 4.00 |
|------------|------|------|------|
| 10 FR | 7425 | 7545 | 7840 |
| 20 FR | 6685 | 6790 | 7055 |
| 30 FR | 5940 | 6035 | 6270 |
| 40 FR | 5305 | 5390 | 5600 |
| 50 FR | 4775 | 4850 | 5000 |
| 10 DW | 5255 | 5340 | 5425 |
| 20 DW | 4730 | 4805 | 4885 |
| 30 DW | 4205 | 4275 | 4340 |
| 40 DW | 3755 | 3815 | 3875 |
| 50 DW | 3380 | 3435 | 3450 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.