

# FLOTATION 648

<b>TIRE SIZE</b>	500/50 - 17
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	BIAS
<b>MACHINERY</b>	HEUPRESSE / ERNTEMASCHINE / STREUMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	137 A8/133 B
<b>LI/SS FREE ROLLING</b>	149 A8/145 B



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94039807	<b>RC (IN)</b>	108.3
<b>SW (IN)</b>	20.1	<b>RIM REC</b>	16.00
<b>OD (IN)</b>	37.2	<b>ECE</b>	E4-106R-001885
<b>SLR (IN)</b>	16.4	<b>PR</b>	14

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	32	35	41
5 FR	8710	9170	10030
10 FR	7840	8240	9030
20 FR	6970	7330	8020
25 FR	6220	6550	7160
30 FR	5600	5900	6390
5 DW	6160	6480	7100
10 DW	5540	5830	6390
20 DW	4930	5180	5680
25 DW	4400	4630	5070
30 DW	3960	4170	4540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.