

# AS 504

<b>TIRE SIZE</b>	<b>11.0/65 - 12</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS DRIVE WHEEL</b>	101 A8
<b>LI/SS FREE ROLLING</b>	114 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	273	<b>RIM REC</b>	9.00
<b>OD (MM)</b>	700	<b>ECE</b>	E4-106R-002834
<b>SLR (MM)</b>	321	<b>PR</b>	8
<b>RC (MM)</b>	2072		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.90
10 FR	1650
25 FR	1405
30 FR	1320
40 FR	1180
10 DW	1155
25 DW	980
30 DW	925
40 DW	825

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.