


# RT 747 AGRO INDUSTRIAL

<b>TYRE SIZE</b>	<b>460/70 R 24</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	COMPACT LOADER / TELEHANDLER / COMPACT LOADER / TELEHANDLER
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	159 A8 ; 156 B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94059270	<b>RC (IN)</b>	151.2
<b>SW (IN)</b>	18.3	<b>RIM REC</b>	DW 15 L
<b>OD (IN)</b>	49.4	<b>RIM ALT</b>	DW 14 L ; DW 16 L
<b>SLR (IN)</b>	21.9	<b>ECE</b>	E11-106R-005105

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	17	23	29	35	41	46	51	58
30	3380	4170	4950	5640	6430	7200	7730	8820
25	3760	4630	5500	6270	7140	8000	8590	9640
20	3910	4820	5720	6530	7430	8320	8930	10030
15	3980	4910	5830	6650	7570	8490	9100	10230
5 CYC	5640	6940	8260	9410	10710	12000	12890	14470
STATIC	8640	10650	12650	14430	16420	18410	19750	22190

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.