



## DATA SHEET

Última  
actualización  
10-07-2026

# TR 135

|                  |                    |
|------------------|--------------------|
| <b>TIRE SIZE</b> | <b>16.9 - 34</b>   |
| <b>UM</b>        | US STANDARD        |
| <b>MACHINERY</b> | TRACTOR / REMOLQUE |
| <b>VERSIÓN</b>   | HD                 |
| <b>TIRE TYPE</b> | TT                 |
| <b>LI/SS</b>     | 142 A8             |



### DIMENSIONES US STANDARD

|                   |          |                |        |
|-------------------|----------|----------------|--------|
| <b>CÓDIGO USA</b> | 94065509 | <b>RC (IN)</b> | 188.7  |
| <b>SW (IN)</b>    | 16.9     | <b>RIM REC</b> | W 15 L |
| <b>OD (IN)</b>    | 62.4     | <b>RIM ALT</b> | W 14 L |
| <b>SLR (IN)</b>   | 28.7     | <b>PR</b>      | 14     |

### LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>41</b> |
| 25               | 2650      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.