


# FL 630 ULTRA

<b>TIRE SIZE</b>	<b>500/60 R 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MAȘINĂ DE ÎMPRĂȘTIAT / CISTERNĂ / REMORCĂ / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	155 D ; 166 A8



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94046065	<b>RC (IN)</b>	141.4
<b>SW (IN)</b>	19.8	<b>RIM REC</b>	AG 16.00
<b>OD (IN)</b>	46.1	<b>RIM ALT</b>	15.00; 16.00; 17.00
<b>SLR (IN)</b>	20.5	<b>ECE</b>	E4-106R-001404

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	23	29	35	41	46	52	58
45	2490	2890	3270	3920	4600	5260	5890	6550	7160	7780
40	2730	3160	3590	4300	5050	5750	6460	7180	7860	7540
30	3320	3840	4340	5170	6110	6970	7800	8690	9510	10340
25	3750	4330	4920	5910	6860	7850	8800	9790	10760	11680
15	4320	5000	5680	6790	7970	9060	10210	11310	12420	13500
5	4930	5700	6460	7720	9040	10360	11570	12900	14150	15380

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.