

# SL 441

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | 200/60 - 14.5                             |
| <b>UM</b>                 | US STANDARD                               |
| <b>CONSTRUCTION</b>       | BIAS                                      |
| <b>MACHINERY</b>          | ARBETSFORDON / SLÄPVAGN /<br>ARBETSFORDON |
| <b>VERSION</b>            | STANDARD                                  |
| <b>TIRE TYPE</b>          | TT  |
| <b>LI/SS FREE ROLLING</b> | 106 A8                                    |



## DIMENSIONER US STANDARD

|                 |          |                |         |
|-----------------|----------|----------------|---------|
| <b>USA CODE</b> | 94011087 | <b>RC (IN)</b> | 70.3    |
| <b>SW (IN)</b>  | 8.3      | <b>RIM REC</b> | AG 6.75 |
| <b>OD (IN)</b>  | 24.0     | <b>PR</b>      | 10      |
| <b>SLR (IN)</b> | 10.9     |                |         |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 73   |
|-----------|------|
| 5 FR      | 2930 |
| 15 FR     | 2490 |
| 20 FR     | 2350 |
| 25 FR     | 2090 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.