

# TR 319

<b>TIRE SIZE</b>	<b>29X12.50 - 15</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / МАШИНА ДЛЯ СБОРА ФРУКТОВ / ТРАНШЕЙНЫЙ ЭКСКАВАТОР / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	98 B



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	312	<b>RIM REC</b>	10 LB
<b>OD (MM)</b>	755	<b>ECE</b>	E11-106R-004604
<b>SLR (MM)</b>	360	<b>PR</b>	6
<b>RC (MM)</b>	2264		

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>2.10</b>
50	750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.