


# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>600/65 R 34</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	157 D ; 160 A8



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	611	<b>RIM REC</b>	DW 20 B
<b>OD (MM)</b>	1644	<b>RIM ALT</b>	W 18 L
<b>SLR (MM)</b>	742	<b>ECE</b>	E4-106R-001405
<b>RC (MM)</b>	4960	<b>SRI</b>	775

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>65</b>	1980	2310	2600	2890	3180	3425	3795	4125
<b>50</b>	2085	2430	2735	3035	3340	3600	3990	4335
<b>40</b>	2160	2520	2835	3150	3465	3735	4140	4500
<b>30</b>	2280	2660	2990	3325	3655	3940	4370	4745
<b>10 LT</b>	2655	3100	3485	3875	4260	4590	5090	5530
<b>10 HT</b>	2280	2660	2990	3325	3655	3940	4370	4745

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.