


# FLOTATION 558

<b>TIRE SIZE</b>	<b>400/55 - 22.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	BALER / HAY HARVESTER / TANKER / TRAILER / HARVESTER / IMPLEMENTS
<b>VERSION</b>	ARAMID BELTED HD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	140 A8/136 B
<b>LI/SS FREE ROLLING</b>	152 A8/148 B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	405	<b>RIM REC</b>	AG 11.75
<b>OD (MM)</b>	1020	<b>RIM ALT</b>	12.25; 13.00; AG 13.00
<b>SLR (MM)</b>	445	<b>ECE</b>	E11-106R-005350
<b>RC (MM)</b>	3084	<b>PR</b>	16

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.70	3.80	4.00
10 FR	4745	4825	4970
20 FR	4270	4340	4475
30 FR	3795	3860	3975
40 FR	3390	3445	3550
50 FR	3050	3100	3150
10 DW	3345	3395	3500
20 DW	3010	3055	3150
30 DW	2675	2715	2800
40 DW	2390	2425	2500
50 DW	2150	2185	2240

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.