

# GRIP STAR

|                           |                         |
|---------------------------|-------------------------|
| <b>TIRE SIZE</b>          | <b>15.5/80 - 24</b>     |
| <b>UM</b>                 | US STANDARD             |
| <b>CONSTRUCTION</b>       | BIAS                    |
| <b>MACHINERY</b>          | SOLLEVATORE TELESCOPICO |
| <b>VERSIONE</b>           | STANDARD                |
| <b>TIRE TYPE</b>          | TT                      |
| <b>LI/SS DRIVE WHEEL</b>  | 151 A6                  |
| <b>LI/SS FREE ROLLING</b> | 163 A6                  |



## DIMENSIONI US STANDARD

|                   |          |                |              |
|-------------------|----------|----------------|--------------|
| <b>CODICE USA</b> | 94048823 | <b>RC (IN)</b> | 145.0        |
| <b>SW (IN)</b>    | 15.4     | <b>RIM REC</b> | W 12         |
| <b>OD (IN)</b>    | 50.0     | <b>RIM ALT</b> | W 13; W 14 L |
| <b>SLR (IN)</b>   | 22.4     | <b>PR</b>      | 16           |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>58</b> |
| <b>20 FR LLV</b> | 10750     |
| <b>20 DW LLV</b> | 7610      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.