

# AW 708

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | <b>19.0/45 - 17</b>   |
| <b>UM</b>                 | US STANDARD   |
| <b>CONSTRUCTION</b>       | ❖ BIAS  |
| <b>MACHINERY</b>          | PRESĂ DE BALOTAT / MAȘINI DE<br>IMPLEMENTARE / REMORCĂ / MAȘINĂ<br>DE RECOLTARE / MAȘINI DE<br>IMPLEMENTARE / REMORCĂ |
| <b>VERSION</b>            | STUBBLE RESISTANT   |
| <b>TIRE TYPE</b>          | TL  |
| <b>LI/SS FREE ROLLING</b> | 152 A8  |



## DIMENSIUNI US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94047697 | <b>RC (IN)</b> | 99.8            |
| <b>SW (IN)</b>  | 18.5     | <b>RIM REC</b> | 16.00           |
| <b>OD (IN)</b>  | 34.1     | <b>ECE</b>     | E11-106R-003636 |
| <b>SLR (IN)</b> | 15.0     | <b>PR</b>      | 22              |

## LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>57</b> |
|------------------|-----------|
| <b>5 FR</b>      | 10960     |
| <b>15 FR</b>     | 9310      |
| <b>20 FR</b>     | 8760      |
| <b>25 FR</b>     | 7830      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.