


RIDEMAX FL 693 M



TIRE SIZE	VF 400/45 R 17.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TANKER / TRAILER / IMPLEMENTS
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	159 D

DIMENSIONS IS STANDARD

SW (MM)	400	RIM REC	14.00
OD (MM)	800	ECE	E11-106R-006068
SLR (MM)	343	SRI	390
RC (MM)	2357		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0	6.0
70	1000	1280	1595	1795	2075	2355	2595	2830	3110	3510	3985
65	1095	1400	1750	1970	2275	2585	2845	3110	3415	3850	4375
50	1325	1695	2120	2385	2755	3125	3445	3760	4135	4660	5295
40	1490	1905	2380	2680	3095	3515	3870	4225	4645	5240	5950
30	1655	2120	2645	2975	3440	3900	4300	4695	5160	5820	6610
25	1730	2215	2770	3115	3600	4080	4495	4910	5395	6090	6915
10	1970	2520	3150	3545	4095	4650	5120	5595	6145	6930	7875

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.