


# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>480/65 R 28</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VINDIMADORA / TRATOR / CEIFEIRA
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	142 D ; 145 A8



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	479	<b>RIM REC</b>	W 15 L
<b>OD (MM)</b>	1335	<b>RIM ALT</b>	W 14 L
<b>SLR (MM)</b>	610	<b>ECE</b>	E4-106R-000653
<b>RC (MM)</b>	4091	<b>SRI</b>	650

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1275	1485	1670	1855	2045	2200	2440	2650
50	1340	1560	1755	1950	2145	2315	2565	2785
40	1395	1625	1830	2030	2235	2410	2670	2900
30	1465	1710	1925	2135	2350	2535	2810	3050
10 LT	1710	1995	2240	2490	2740	2955	3275	3555
10 HT	1465	1710	1925	2135	2350	2535	2810	3050

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.