


# AGRIMAX SPARGO SB

TIRE SIZE	VF 270/95 R 32
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ТРАКТОР-ТЯГАЧ / ОПРЫСКИВАТЕЛЬ
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	148 D



## РАЗМЕРЫ US STANDARD

USA CODE	94076352	RC (IN)	160.6
SW (IN)	11.0	RIM REC	W9
OD (IN)	52.7	ECE	E11-106R-0010499
SLR (IN)	24.3		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	14	17	20	23	29	35	41	46	52	58
45	2980	3370	3740	4060	4500	4760	5200	5640	6020	6330
FROM 40 TO 25	3280	3690	4110	4460	4940	5220	5700	6190	6610	6950
20	3340	3760	4190	4550	5040	5330	5820	6320	6740	7090
12	3410	3840	4280	4630	5140	5430	5940	6440	6880	7240
5	3600	4060	4510	4900	5440	5740	6280	6810	7270	7640

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.