


EARTHMAX SR 22



| | |
|---------------------|--|
| TIRE SIZE | 17.5 R 25 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | NIVELEUSE / CHARGEUR / BULLDOZER / CHARGEUR / BULLDOZER / NIVELEUSE |
| VERSION | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 167 B ; 182 A2 |

DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|--------------------|-----------|
| CODE USA | 94052387 | RIM REC | 14.00/1.5 |
| OD (IN) | 53.1 | TRA CODE | E2/L2 |
| SLR (IN) | 23.2 | STAR RATING | ★★ |
| RC (IN) | 155.5 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 58 | 62 | 65 | 69 | 73 | 76 | 80 | 83 | 87 | 91 | 94 |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 9650 | 10200 | 10500 | 11000 | 11400 | 12000 | -- | -- | -- | -- | -- |
| 5 | -- | -- | -- | -- | -- | 16100 | 16500 | 17100 | 17600 | 18200 | 18700 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.