



Latest update  
10-07-2026

## DATA SHEET

# TR 135

|                  |                   |
|------------------|-------------------|
| <b>TIRE SIZE</b> | <b>23.1 - 30</b>  |
| <b>UM</b>        | US STANDARD       |
| <b>MACHINERY</b> | TRACTOR / TRAILER |
| <b>VERSION</b>   | STANDARD          |
| <b>TL/TT</b>     | TL                |
| <b>LI/SS</b>     | 151 A8            |



### DIMENSIONS US STANDARD

|                 |          |                |                   |
|-----------------|----------|----------------|-------------------|
| <b>USA CODE</b> | 94004065 | <b>RC (IN)</b> | 205.4             |
| <b>SW (IN)</b>  | 23.6     | <b>RIM REC</b> | DW 20 B ; DW 20 A |
| <b>OD (IN)</b>  | 66.9     | <b>ECE</b>     | E4-106R-002302    |
| <b>SLR (IN)</b> | 30.4     | <b>PR</b>      | 12                |

### LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>24</b> |
| 25               | 7600      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.