

# AGRIMAX RT 855

|                  |                                                                       |
|------------------|-----------------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>460/85 R 38</b>                                                    |
| <b>UM</b>        | US STANDARD                                                           |
| <b>MACHINERY</b> | SPRAYER / VINEYARD HARVESTER /<br>TRACTOR / HARVESTER /<br>IMPLEMENTS |
| <b>VERSION</b>   | STANDARD                                                              |
| <b>TL/TT</b>     | TL                                                                    |
| <b>LI/SS</b>     | 149 A8/B                                                              |



## DIMENSIONS US STANDARD

|                 |          |                                      |                 |
|-----------------|----------|--------------------------------------|-----------------|
| <b>USA CODE</b> | 94021789 | <b>RIM REC</b>                       | W 16 L          |
| <b>SW (IN)</b>  | 18.7     | <b>RIM ALT</b>                       | W 14 L ; W 15 L |
| <b>OD (IN)</b>  | 68.8     | <b>ECE</b>                           | E4-106R-000618  |
| <b>SLR (IN)</b> | 30.9     | <b>TRA CODE</b>                      | R1W             |
| <b>RC (IN)</b>  | 204.9    | <b>TREAD DEPTH (32<sup>nd</sup>)</b> | 67.41           |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI   | 9    | 12   | 15   | 17   | 20   | 23   |
|-------------|------|------|------|------|------|------|
| <b>30</b>   | 3950 | 4590 | 5240 | 5870 | 6530 | 7160 |
| <b>25</b>   | 3950 | 4590 | 5240 | 5870 | 6530 | 7160 |
| <b>20</b>   | 4220 | 4920 | 5610 | 6290 | 6990 | 7670 |
| <b>5 LT</b> | 5290 | 6150 | 7010 | 7880 | 8740 | 9600 |
| <b>5 HT</b> | 4220 | 4920 | 5610 | 6290 | 6990 | 7670 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.