

# FLOTATION V LINE

|                           |                                    |
|---------------------------|------------------------------------|
| <b>TIRE SIZE</b>          | <b>500/60 - 22.5</b>               |
| <b>UM</b>                 | IS STANDARD                        |
| <b>CONSTRUCTION</b>       | ❖ BIAS                             |
| <b>MACHINERY</b>          | REBOQUE / IMPLEMENTOS<br>AGRÍCOLAS |
| <b>VERSÃO</b>             | STANDARD                           |
| <b>TIRE TYPE</b>          | TL                                 |
| <b>LI/SS DRIVE WHEEL</b>  | 145 A8/142 B                       |
| <b>LI/SS FREE ROLLING</b> | 157 A8/154 B                       |



## DIMENSÕES IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 500  | <b>RIM REC</b> | AG 16.00       |
| <b>OD (MM)</b>  | 1170 | <b>RIM ALT</b> | 15.00; 17.00   |
| <b>SLR (MM)</b> | 510  | <b>ECE</b>     | E4-106R-001561 |
| <b>RC (MM)</b>  | 3489 | <b>PR</b>      | 12             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.50 | 2.00 | 2.40 |
|------------|------|------|------|
| 10 FR      | 4390 | 5195 | 5775 |
| 20 FR      | 3950 | 4675 | 5200 |
| 30 FR      | 3510 | 4155 | 4620 |
| 40 FR      | 3135 | 3710 | 4125 |
| 50 FR      | 2820 | 3340 | 3750 |
| 10 DW      | 3085 | 3645 | 4060 |
| 20 DW      | 2780 | 3280 | 3655 |
| 30 DW      | 2470 | 2920 | 3250 |
| 40 DW      | 2205 | 2605 | 2900 |
| 50 DW      | 1985 | 2345 | 2650 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.