

# AW 702

<b>TIRE SIZE</b>	<b>13.0/55 - 16</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	138 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94009732	<b>RC (IN)</b>	88.8
<b>SW (IN)</b>	13.2	<b>RIM REC</b>	11.0
<b>OD (IN)</b>	30.3	<b>ECE</b>	E4-106R-002332
<b>SLR (IN)</b>	13.6	<b>PR</b>	18

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>78</b>
5 FR	7290
15 FR	6190
20 FR	5830
25 FR	5200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.