


# FL 639

<b>TIRE SIZE</b>	<b>600/50 R 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SPRIDARE / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	168 B ; 156 B



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94063239	<b>RC (IN)</b>	141.4
<b>SW (IN)</b>	24.1	<b>RIM REC</b>	AG 20.00
<b>OD (IN)</b>	46.1	<b>ECE</b>	E11-106R-006478
<b>SLR (IN)</b>	20.5		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	20	23	26	29	32	35	38	41	44	46
<b>30 FR</b>	4800	5475	6150	6875	7600	8200	8800	9500	10200	10800	11400	11850	12300
<b>30 DW</b>	3420	3910	4400	4880	5360	5755	6150	6650	7150	7600	8050	8425	8800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.