

# AGRIMAX RT 855

**320/85 R 38****UM** US STANDARD**CONSTRUCTION**  RADIAL**MACHINERY** İLAÇLAMA / ÜZÜM HASAT MAKİNESİ /  
TRAKTÖR / BIÇERDÖVER /  
UYGULAMALI MAKİNE**VERSION** SPECIAL**TIRE TYPE** TL

143 A8/B



## UNDEFINED US STANDARD

<b>USA CODE</b>	94047543	<b>RC (IN)</b>	180.3
<b>SW (IN)</b>	13.0	<b>RIM REC</b>	W 11
<b>OD (IN)</b>	59.4	<b>RIM ALT</b>	W 9 ; W 10 ; DW 10
<b>SLR (IN)</b>	27.6	<b>ECE</b>	E4-106R-000781

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	17	23	29	35	41	46	52
30	2170	2520	3310	4030	4390	4700	5110	5530	6000
25	2170	2520	3310	4030	4390	4700	5110	5530	6000
20	2330	2710	3550	4320	4710	5030	5480	5930	6440
5 LT	2910	3390	4440	5400	5890	6290	6860	7420	8060
5 HT	2330	2710	3550	4320	4710	5030	5480	5930	6440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.