



IS standard



EARTHMAX

RADIAL OTR TIRES

SR 30 M



PRODUCT DATA SHEET

EARTHMAX SR 30 M

RADIAL OTR TIRES



EARTHMAX SR 30 M is an All-Steel radial tyre specifically engineered for medium-sized wheel loaders operating primarily at industrial sites and factories on smooth, paved surfaces but also travelling occasionally on public roads. Thanks to its versatility, ensured by the tread pattern and compound, the tyre provides reliable performance on both hard surfaces and uneven terrain, making it suitable for mixed applications in industrial, construction, and civil environments. EARTHMAX SR 30 M features an optimized tread design that minimizes vibrations and noise, ensuring superior driving comfort and a smooth ride, especially over longer distances. In addition, the reduced rolling resistance provides enhanced fuel efficiency and contributes to lower operating costs during transport and load & carry operations.

-  Radial
-  E-3/L-3
-  B
-  195

Technologies



Performance

-  Traction
-  Cut Resistance
-  Stability
-  Durability
-  Fuel Economy
-  Comfort

	Tyre size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
Ø 25"	23.5 R 25	TL	E-3/L-3	**/*	185 B/195 A2	CRC	210	605	1605	711	4797	34	19.50/2.5	-

CRC: Cut Resistance Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference

BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment. All images, texts and graphics contained in this brochure are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. EN-GB / 05-2026