


AGRIMAX RT 855

| | |
|---------------------|--|
| TIRE SIZE | 480/80 R 38 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 149 A8/B |



DIMENSIUNI US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94045341 | RC (IN) | 203.2 |
| SW (IN) | 18.7 | RIM REC | DW 16 L |
| OD (IN) | 68.8 | RIM ALT | W 14 L; W 15 L |
| SLR (IN) | 30.9 | ECE | E4-106R-001822 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|------|------|------|------|------|
| 30 | 3950 | 4590 | 5240 | 5870 | 6530 | 7160 |
| 25 | 3950 | 4590 | 5240 | 5870 | 6530 | 7160 |
| 20 | 4220 | 4920 | 5610 | 6290 | 6990 | 7670 |
| 5 LT | 5290 | 6150 | 7010 | 7880 | 8740 | 9600 |
| 5 HT | 4220 | 4920 | 5610 | 6290 | 6990 | 7670 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.