


# EARTHMAX SR 57

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>18.00 R 25</b>  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | DOZER / PALA LHD / PALA<br>CARICATRICE   |
| <b>VERSIONE</b>     | CUT RESISTANT COMPOUND   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 204 A2   |



## DIMENSIONI IS STANDARD

|                    |           |
|--------------------|-----------|
| <b>OD (MM)</b>     | 1651      |
| <b>RIM REC</b>     | 13.00/2.5 |
| <b>TRA CODE</b>    | L5        |
| <b>STAR RATING</b> | ★★        |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 5.75  | 6.00  | 6.25  | 6.50  | 6.75  | 7.00  | 7.25  | 7.50  | 7.75  | 8.00  | 8.25  |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 10         | 12150 | 12500 | 12850 | 13200 | 13600 | 14000 | 14500 | 15000 | 15250 | 15500 | 16000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.