

# FL 630 SUPER

<b>TIRE SIZE</b>	<b>710/50 R 30.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MAȘINĂ DE ÎMPRĂȘTIAT / CISTERNĂ / REMORCĂ / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	173 D



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	686	<b>RIM REC</b>	AG 20.00
<b>OD (MM)</b>	1485	<b>RIM ALT</b>	AG 24.00
<b>SLR (MM)</b>	676	<b>ECE</b>	E11-106R-0010340
<b>RC (MM)</b>	4550	<b>SRI</b>	700

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1835	2130	2430	3020	3435	4025	4500	4910	5385	5915
65	2015	2340	2665	3315	3770	4420	4940	5395	5915	6500
50	2440	2835	3225	4015	4565	5350	5980	6530	7160	7865
40	2745	3185	3625	4510	5130	6015	6720	7340	8045	8840
25	3185	3700	4215	5240	5960	6985	7810	8525	9350	10270
10	3630	4215	4800	5970	6790	7960	8895	9715	10650	11700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.