



PRINTED ON
23-04-2026

DATA SHEET

TR 461

| | |
|---------------------------|------------------------------|
| TIRE SIZE | 15.5/80 - 18 |
| UM | US STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | TELEHANDLER / BACKHOE LOADER |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 138 A8 |
| LI/SS FREE ROLLING | 150 A8 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94067428 | RC (IN) | 114.3 |
| SW (IN) | 12.0 | RIM REC | W 9 |
| OD (IN) | 38.9 | RIM ALT | 11 |
| SLR (IN) | 17.1 | ECE | E11-106R-006914 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 80 |
|------------------|-----------|
| 5 FR | 10340 |
| 15 FR | 8780 |
| 20 FR | 8270 |
| 25 FR | 7390 |
| 5 DW | 7290 |
| 15 DW | 6190 |
| 20 DW | 5830 |
| 25 DW | 5200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.